



CODE	FLOW RATE (L/min.)	PRESSURE MAX (BAR)	CAPACITY TANK (L)	DIGITAL FLOW METER	LIQUID	PRESSURE SETTING
CPR	7,5	50	30		50% H2O + 50% GLICOLE	✓
CPR C60-P30D	30	40	60	✓	50% H2O + 50% GLICOLE	✓
CPR C60-P60D	60	20	60	✓	50% H2O + 50% GLICOLE	✓
CPR H2O C60 P25	25	10	60		H2O	

CPR cooling test station is an easy and effective tool to check the thermoregulation circuits hydraulic seal.

It is possible to carry out the test closing the tap that cut off the flow circulation allowing the pump to generate pressure inside the circuit, the pressure can be adjusted by the means of a relief valve. Once the desired test pressure has been achieved the feeding tap has to be closed and the engine switched off. In such situation a leakage in the circuits immediately produces a pressure drop inside the circuit shown by a manometer. Once the test is over it is possible to empty the circuit by the mean of compressed air that push the liquid back into the CPR tank.

In order to verify the flow rate inside each circuit at a defined pressure it is necessary to equip the CPR with pump and engine able to guarantee a higher flow rate. The circulating pressure will be defined by the circuit geometry and can be adjusted to reach the desired value thanks to a relief valve. In order to have a more flexible system it is possible to equip the CPR machine with a frequency drive system able to modify the rpm of the engine and accordingly the flow rate. Such CPR machines are equipped with digital flow meter and with a by-pass system able to protect the flow meter while using compressed air to empty the circuit.



**BNC  
COMPONENTS  
LTD**

248392 Sideroad # 5,  
Mono, Ontario, L9W 6L2

1 (888) 580-0011 (toll-free)  
1 (905) 822-1161 (local)

[sales@bnccomponents.com](mailto:sales@bnccomponents.com)

**ERMANN BALZI srl**  
componenti e accessori per stampi

 **Made in Italy**